

STINGER®

BULLHEAD SAFETY® EYE PROTECTION

BH691PFT

PFT
PERFORMANCE FOG TECHNOLOGY



BH6G

Optional flame resistant foam gasket for Stinger® styles

BH6FBG

Optional flame resistant foam brow gasket for Stinger® styles

LENS Clear Performance Fog Technology

FRAME Shiny Pearl Gray

DESCRIPTION

The rugged design of the Stinger® safety glasses features rigid TPR flared temple ends, soft nose pieces, and properly placed ventilation ports to reduce fogging. With a single 9 base curve lens, it is designed for maximum impact resistance and superior side coverage. The BH691PFT also features a PFT lens. Thanks to its chemical and physical properties, Performance Fog Technology is a permanent coating that prevents the formation of condensation on the lenses by absorbing the humidity drops.

BH6G - Optional flame-resistant foam gasket for all Stinger® styles.

BH6FBG - Optional flame resistant foam brow gasket for all Stinger® styles

FEATURES

- PFT - Performance Fog Technology lens: Better than traditional anti-fog! This water-washable, hydrophilic anti-fog lens coating is permanently bonded to the lens to absorb moisture and then spread it consistently, providing clear, fog-free vision
- Rugged design for maximum resistance
- 9 base curve for superior side coverage
- Rigid, flared TPR temple ends for a secure fit
- Soft TPR nose pieces prevent slippage

TECHNOLOGY

All Bullhead Safety® Eyewear is made from 100% virgin materials. This style features lenses and frames constructed with the highest quality polycarbonate.



MEETS ANSI/ISEA
Z87.1-2020
STANDARDS



MEETS
ANTI-FOG
STANDARD



ARC FLASH
TESTED TO
35 CAL/CM²



MEETS MILITARY
SPECS FOR
BALLISTICS



ERGONOMIC FIT
RELIEVES
PRESSURE



ANTI-SCRATCH
HARD COAT
TREATED LENS



PERMANENT
HYDROPHILIC
COATING



TAPERED LENS
ELIMINATES
DISTORTION



FILTERS 99.9%
UVA/UVB/UVC
LIGHT RAYS



PROVIDES SEAL
AGAINST DEBRIS
AND IMPACT

*Optional

- Meets ANSI/ISEA Z87.1-2020 standards
- Meets ANSI/ISEA Z87.1-2020 anti-fog properties standard

SPECIFICATIONS

LENS	LIGHT TRANSMITTANCE	FRAME TYPE	FRAME COLOR	WEIGHT	BASE CURVE	FRAME WIDTH	TEMPLE LENGTH	END OF TIPS WIDTH
Clear PFT	89%	Vented Half Frame	Shiny Pearl Gray	30 Grams	9	142 mm	120 mm	90 mm

PACKAGING

	EACH	INNER PACK	CASE
QUANTITY	1	12/box	12 boxes/case
UPC/GTIN	816368026282	10816368026289	20816368026286

13915 Radium St NW
Ramsey, MN 55303

763-450-0110
Sales@BullheadSafety.com

BullheadSafety.com

